

# The smallest automatic lubricator

In confined spaces, the 15 ml simalube offers the perfect solution. With its compact size, it is unique on the global market as the smallest automatic lubricator. It functions the same as the larger simalube lubricators and offers the same advantages.

# Small size delivers big performance

- Space-saving thanks to compact size
- Robust aluminium enclosure
- Same refill, installation and function as other simalube lubricators
- Alternative to the simalube multipoint when less than 5 lubrication points are needed (see page 7)

G 1/4"

### **Dimensions**

# Drive Pressure chamber Piston Housing Label Lubricant O 0.87 in Connection

## **Specifications**

| Product               | Automatic, long-term grease and oil lubricator   |
|-----------------------|--|
| Power generation      | Hydrogen gas producing<br>drycell  |
| Working pressure      | Max. 72.5 psi  |
| Adjustment            | Stepless 1–12 months<br>(for standard conditions)  |
| Operating temperature | -4 °F to +131 °F ambient temperature<br>(Grease consistency changes with<br>temperature) |
| Storage temperature   | Recommended at 68 °F ±41 °F  |
| Lubricator volume     | 0.51 fl.oz.  |
| Weight full/empty     | ~1.3 oz / ~0.8 oz  |
| Certifications        | ( <b>E IP EX</b>   |